

# IPC-D-1143G2-LU-C

Dome Network Camera



## Features

---

- HiView
- IP Dome Camera
- 1/2.8" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0 Lux
- Hybrid light: IR and white light
- Hybrid light range 20 m
- Compression H.265+ / H.265 / H.264+ / H.264
- Motion detection 2.0: human detection
- DWDR
- 3D DNR
- Integrated microphone
- RJ-45 10/100M BaseT
- PoE IEEE802.3af
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Suitable for interior

## Specifications

<b>Brand</b>	HiView
<b>Image sensor</b>	1/2.8" Progressive Scan CMOS
<b>Maximum resolution</b>	4 Megapixel (2560x1440)
<b>Main Stream rate</b>	20 fps (2560x1440), 25 fps (1920x1080, 1280x720)
<b>Extra Stream rate</b>	25 fps (1280x720, 640x480, 640x360)
<b>Compression</b>	H.265+ / H.264+ / H.265 / H.264
<b>Bitrate</b>	32 Kbps ~ 8 Mbps
<b>Lens</b>	2.8 mm
<b>Viewing Angle (FOV)</b>	H: 104°, V: 57°, D: 123°
<b>Range performance</b>	53 m (D), 21 m (O), 10 m (R), 5 m (I)
<b>Minimum illumination</b>	Colour: 0.01 Lux @(F2.2, AGC ON) 0 Lux with IR range 20 m
<b>Supplementary lighting</b>	Hybrid light: IR Range 20 m White light range 20 m
<b>Day/Night</b>	Removable mechanical ICR filter
<b>Image improvements</b>	DWDR, BLC, HLC, 3D-DNR, AGC, AWB, ROI, Mirror function, Privacy masking
<b>Motion Detection</b>	Motion detection 2.0 with human classification applied in motion detection.
<b>Internal memory</b>	Does not have
<b>Audio</b>	Integrated microphone
<b>Audio type</b>	Mono
<b>Audio Compression</b>	G.711ulaw/AAC-LC
<b>Audio bitrate</b>	64 Kbps (G.711ulaw)/16 a 64 Kbps (AAC-LC)
<b>Network interface</b>	Ethernet 10/100M BaseT
<b>Remote access</b>	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
<b>Interoperability</b>	ONVIF, ISAPI
<b>Power</b>	DC 12 V / 500 mA / 6 W max. / IEEE802.3af PoE

<b>Degree of protection</b>	Suitable for interior
<b>Material</b>	Plastic
<b>Temp. operation</b>	-30° C ~ +60° C
<b>Dimensions</b>	Ø 121.5 mm x 97.6 (H) mm
<b>Base dimensions</b>	Ø base 121.5 mm / Ø entre tornillos 104.7 mm / 3 tornillos
<b>Weight</b>	570 g